

E-Z Guide

Fire Hydrant Safety Markers

Product Specification

E-Z Fold Fiberglass Markers

Scope:

This specification sheet covers the manufacturers' requirements for the fiberglass safety markers. All markers meet or exceed industry standards and requirements

Materials:

3/8" Rigid solid pultrusion fiberglass rod coated with Sunguard II™ UV inhibitor.

3/8" MIL SPEC Zinc Plated Carbon Steel
Original hinge design with optional locking mechanism and integrated bracket designed for direct mounting

3M Scotchlite™ Engineer Grade Reflective Sheeting, DOT Certified used for reflective material on rod.

Marking:

All markers must have a minimum of 8 - 6" wide alternating strips of 3M™ Scotchlite Red 3272 and White 3290 reflective sheeting.

All markers must have safety yellow rubber protective tip and spring bonnet.

E-Z Fold Aluminum Markers

Scope:

This specification sheet covers the manufacturers' requirements for the aluminum safety markers. All markers meet or exceed industry standards and requirements

Materials:

3/8" Rigid 6061 solid aluminum rod.

3/8" MIL SPEC Zinc Plated Carbon Steel
Original hinge design with optional locking mechanism and integrated bracket designed for direct mounting

3M Scotchlite™ Engineer Grade Reflective Sheeting, DOT Certified used for reflective material on rod.

Marking:

All markers must have a minimum of 8 - 6" wide alternating strips of 3M™ Scotchlite Red 3272 and White 3290 reflective sheeting.

All markers must have safety yellow rubber protective tip and spring bonnet.

